

Model Range Specifications E5 NX series

| | E5 20.3 | E5 20.4 | E5 25.3 | E5 25.4 | E5 25.3 T | E5 25.4 T | E5 25.3 P | E5 25.4 P |
|---|-------------------|-------------------|-------------------|-------------------|-----------------------|-----------------------|-------------------|-------------------|
| 1 CAPACITY @ 600mm LOAD CENTRE | 2000 (KG) | 2000 (KG) | 2500 (KG) | 2500 (KG) | 2500 (KG) | 2500 (KG) | 2500 (KG) | 2500 (KG) |
| 2 BATTERY | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah | 11kWh 220Ah |
| 3 CHARGER | 1.8kW | 1.8kW | 1.8kW | 1.8kW | 1.8kW | 1.8kW | 1.8kW | 1.8kW |
| 4 ELECTRICAL SYSTEM | 48V / 12V | 48V / 12V | 48V / 12V | 48V / 12V | 48V / 12V | 48V / 12V | 48V / 12V | 48V / 12V |
| 5 DRIVE WHEELS | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 6 STEERING | Hydrostatic | Hydrostatic | Hydrostatic | Hydrostatic | Hydrostatic | Hydrostatic | Hydrostatic | Hydrostatic |
| 7 TYRES | 27 x10-12 | 27 x10.5-15 | 27 x10-12 | 27 x10.5-15 | 27 x10-12 | 27 x10.5-15 | 27 x10-12 | 27 x10.5-15 |
| 8 OUTSIDE DIAMETER | 680 mm | 680 mm | 680 mm | 680 mm | 680 mm | 680 mm | 680 mm | 680 mm |
| 9 WIDTH | 255 mm | 255 mm | 255 mm | 255 mm | 255 mm | 255 mm | 255 mm | 255 mm |
| 10 MAXIMUM SPEED | 10 km/h | 10 km/h | 10 km/h | 10 km/h | 10 km/h | 10 km/h | 10 km/h | 10 km/h |
| 11 MAXIMUM GRADABILITY (4 Way Mode) | 30% | 30% (15%) | 30% | 30% (15%) | 30% | 30% (15%) | 30% | 30% (15%) |
| 12 TURNING RADIUS | 2320 mm | 2320 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm |
| 13 UNLADEN WEIGHT (3M LIFT HEIGHT) | 2250 kg | 2400 kg | 2365 kg | 2520 kg | 2525 kg | 2585 kg | 2680kg | 2830kg |
| 14 WORKING PRESSURE FOR ATTACHMENTS (BAR) | 180 | 180 | 180 | 180 | 180 | 180 | 180 | 180 |
| 15 TILT OF MAST (FORWARD / BACK) | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees | 7 / 6 degrees |
| 16 SIDESHIFT | 130 mm | 130 mm | 130 mm | 130 mm | 130 mm | 130 mm | 130 mm | 130 mm |
| 17 FORK SECTION | 40 x 100 x 1150mm | 40 x 100 x 1150mm | 50 x 100 x 1150mm | 50 x 100 x 1150mm | 1350x170x56 (1000 St) | 1350x170x56 (1000 St) | 50 x 100 x 1150mm | 50 x 100 x 1150mm |
| 18 MAST CARRIAGE TRAVEL (REACH) | 860 mm | 860 mm | 900 mm | 900 mm | 900 mm | 900 mm | 900 mm (1000mm) | 900 mm (1000mm) |
| A HEIGHT TO TOP OF CANOPY | 2425 mm | 2425 mm | 2425 mm | 2425 mm | 2425 mm | 2425 mm | 2425 mm | 2425 mm |
| B FORK CARRIAGE WIDTH (CLASS) | 1200 mm | 1200 mm | 1200 mm | 1200 mm | 1200 mm | 1200 mm | 1200 mm | 1200 mm |
| C FRAME OPENING | 1540 mm | 1440 mm | 1540 mm | 1440 mm | 1540 mm | 1440 mm | 1540 mm | 1440 mm |
| D/D4 OVERALL WIDTH /4 WAY MODE | 2400 mm | 2440 mm / 2620 mm | 2400 mm | 2440 mm / 2620 mm | 2400 mm | 2440 mm / 2620 mm | 2400 mm | 2440 mm / 2620 mm |
| E OVERHANG (Rear Wheel Turned 180°) | 1200 mm | 1200 mm | 1250 mm | 1250 mm | 1250 mm | 1250 mm | 1350 mm | 1350 mm |
| F WHEEL BASE | 1525 mm | 1525 mm | 1625 mm | 1625 mm | 1625 mm | 1625 mm | 1625 mm | 1625 mm |
| G C. OF G. FROM FORK FACE | 350 mm | 340 mm | 370 mm | 380 mm | 320 mm | 380 mm | 410 mm | 430 mm |
| H1 LIFT HEIGHT (3M) | 3020 mm | 3020 mm | 3020 mm | 3020 mm | 3020 mm | 3020 mm | 3020 mm | 3020 mm |
| H2 MAST HEIGHT COLLAPSED (3M) | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm | 2420 mm |
| H3 MAST HEIGHT RAISED (3M) | 3930 mm | 3930 mm | 3930 mm | 3930 mm | 3930 mm | 3930 mm | 4530 mm | 4530 mm |
| J GROUND CLEARANCE | 180 mm | 180 mm | 180 mm | 180 mm | 180 mm | 180 mm | 180 mm | 180 mm |
| K FACE OF FORK TO CENTRE OF FRONT TYRE | 460 mm | 460 mm | 525 mm | 525 mm | 525 mm | 525 mm | 460 mm | 460 mm |

The above specifications are not binding upon the manufacturer and may be changed without prior notice.
 (1) TREAD PATTERNS: T.G.=Tractor Grip R.T.=Rough Terrain S.S.=Skid Steer S.F.=Super Float
 Weights may vary depending on and/or fork option.

