



Electric pedestrian stacker **EJC 112i**

 JUNGHEINRICH

EJC 112i

	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	2300 mm	1650 mm	100 mm	2775 mm
	2500 mm	1750 mm	100 mm	2975 mm
	2700 mm	1850 mm	100 mm	3175 mm
	2900 mm	1950 mm	100 mm	3375 mm
	3200 mm	2100 mm	100 mm	3675 mm
	3600 mm	2300 mm	100 mm	4075 mm
	3900 mm	2450 mm	100 mm	4375 mm
	4100 mm	2550 mm	100 mm	4575 mm
	4300 mm	2650 mm	100 mm	4775 mm
Duplex mast ZZ	2300 mm	1600 mm	1125 mm	2975 mm
	2500 mm	1700 mm	1225 mm	2975 mm
	2900 mm	1900 mm	1425 mm	3375 mm
	3200 mm	2050 mm	1575 mm	3675 mm
	3600 mm	2250 mm	1775 mm	4075 mm
	3900 mm	2400 mm	1925 mm	4375 mm
Triplex mast DZ	4090 mm	1845 mm	1338 mm	4597 mm
	4300 mm	1915 mm	1408 mm	4807 mm
	4700 mm	2050 mm	1543 mm	5207 mm

VDI table

Stand-on: 10/2023


Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich	
	1.2	Manufacturer's type designation		EJC 112i	
	1.3	Drive		Electric	
	1.4	Operation		Pedestrian	
	1.5	Load capacity/load	Q	kg	1200
	1.6	Load centre distance	c	mm	600
	1.8	Load distance, centre of drive axle to fork	x	mm	707
	1.9	Wheelbase	y	mm	1141
	Weights	2.1.1	Service weight (incl. battery)		kg
2.2		Axle load laden front/rear		kg	590 / 1305
2.3		Axle load unladen front/rear		kg	480 / 215
Wheels/suspension system	3.1	Tyres			Polyurethane (PU)
	3.2	Tyre size, front			Ø 230 x 70
	3.3	Tyre size, rear			Ø 75 x 105
	3.4	Additional wheels			Ø 140 x 54
	3.5	Wheels, number front/back (x=driven)			1x +1/2
	3.6	Tread width, front	b10	mm	507
	3.7	Tread width, rear	b11	mm	405
Basic dimensions	4.2	Retracted mast height (h1)	h1	mm	1950
	4.3	Free lift (h2)	h2	mm	100
	4.4	Lift (h3)	h3	mm	2900
	4.5	Extended mast height (h4)	h4	mm	3375
	4.9	Height of tiller handle in drive position min./max.	h14	mm	750 / 1260
	4.15	Height, lowered	h13	mm	90
	4.19	total length	l1	mm	1754
	4.20	Length including fork shank	l2	mm	604
	4.21.1	total width	b1	mm	800
	4.22	Fork dimensions	s/e/l	mm	60 x 178 x 1150
	4.25	Width across forks	b5	mm	570
	4.32	Ground clearance centre of wheelbase	m2	mm	24
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2002
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2052
	4.35	Turning radius	Wa	mm	1359
Performance data	5.1	Travel speed laden/unladen		km/h	6 / 6
	5.2	Lift speed laden/unladen		m/s	0.17 / 0.33
	5.3	Lowering speed laden/unladen		m/s	0.45 / 0.37
	5.8	Max. gradeability laden/unladen		%	5 / 10
	5.10	Service brake			generative
E-motor/Electronics	6.1	Drive motor, performance S2 60 min		kW	0.9
	6.2	Lift motor, performance with S3		kW	2.8
	6.3	Battery according to DIN 43531/35/36			no
	6.4	Battery voltage/nominal capacity		V / Ah	24 / 100
	6.5	Battery weight		kg	26
	6.6.1	Energy consumption according to EN cycle		kWh/h	0.66
	6.6.2	CO2 equivalent as per EN 16796		kg/h	0.4

Other	8.1	Type of drive control	AC
<p>- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.</p>			

The values in the table apply for the XSi battery compartment, ZT2900 mast, battery 100 Ah.

- VDI no. 1.8: with DZ mast: x - 40 mm
- VDI no. 1.9: with Si battery compartment: y + 50 mm.
- VDI no. 4.19: with Si battery compartment: l1 + 50 mm. with DZ mast: l1 + 40 mm.
- VDI no. 4.20: with Si battery compartment: l2 + 50 mm. with DZ mast: l2 + 40 mm.
- VDI no. 4.34.1: with Si battery compartment: l2 + 48 mm. With DZ mast: aisle width + 40 mm.
- VDI no. 4.34.2: with M Li-ion battery compartment: l2 + 48 mm. With DZ mast: aisle width + 40 mm.
- VDI no. 4.35: with Si battery compartment: l2 + 48 mm.
- VDI no. 6.2: With EJC 112i: S3 12%.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements. 

 **JUNGHEINRICH**